



40XX SERIES Advanced Purification System

4002, 4004, 4005, 4007 & 4030 Purifier Models



- Plug and play installation and activation
- Ultra-Low Energy efficiency <math><0.65\text{Amps}</math> (78.0w 120V 1PH)
- Touch screen controller
- Dynamic monitoring control with internal/external controller and sensor
- Easy maintenance
- Logging available for reporting
- Portable Option

How it Works:

**Existing Air
(Containing Microorganisms)**



**ROS
(Reactive Oxygen Species)**

The sanitized air that comes out of the purifier enters the environment and continues to sanitize ALL surfaces it contacts.

AirROS purifiers utilize electricity and create ROS. The highly-reactive ROS inside the purifier DESTROYS Molds, Pathogens, Viruses, and Odors as they pass through the chamber.

40XX Series Surface & Air Purifiers will sanitize indoor air & surfaces in rooms 550-30,000 cubic feet using less than 0.70Amps (78.0 watts)

► Model Number

- 4002 2,500 ft³ * 4004 4,000 ft³ *
- 4005 5,500 ft³ * 4007 7,500 ft³ *
- 4030 30,000 ft³ *
- C Controller - Touch Screen Controller
- S Sensor - Ozone †
- P Portable - Handle/feet
- I Internal Controller option
- T Transparent Controller Lid w/ SS Latch
- R Remote Sensor option

► Benefits:

- Destroys Mold, Bacteria, Yeast, Pathogens, & Viruses
- Eliminates/neutralizes Odor
- Organic no-chemicals added
- Reduces cross-contamination
- Ultra-low power consumption

Example Configurations:

4005CS
4007C-P
4030/4000CSI
4030/4000CIT/4000S

Dimensions: 16w x 12h x 7d (16w x 13.7h x 7d Portable)

Standard Wall mount
3inch (3.5"OD) PVC Sch40 Output

† Internal or External sensor required for dynamic control
* Actual Capacity depends on Oxygen level, Temp, and Commodity factors



40XX



40XX-P



40XXC



40XXC-P



40XXCS



40XXCS-P



4000CSI
4000S



4000CITR

40XX SERIES

Model	Capacity ft ³	Weight	Amps	Watts
4002 (-P)	2,500	13.8 (15.0)	0.15	17.5
4002C (-P)	2,500	14.2 (15.4)	0.15	18.0
4002CS (-P)	2,500	14.4 (15.6)	0.22	26.4
4004 (-P)	4,000	13.8 (15.0)	0.15	17.5
4004C (-P)	4,000	14.2 (15.4)	0.15	18.0
4004CS (-P)	4,000	14.4 (15.6)	0.22	26.4
4005 (-P)	5,500	11.6 (12.8)	0.16	19.2
4005C (-P)	5,500	12.0 (13.2)	0.18	21.6
4005CS (-P)	5,500	12.2 (13.4)	0.23	27.6
4007 (-P)	7,500	13.8 (15.0)	0.15	17.5
4007C (-P)	7,500	14.2 (15.4)	0.15	18.0
4007CS (-P)	7,500	14.4 (15.6)	0.22	26.4
4030 (-P)	30,000	10.0 (11.2)	0.58	69.5
4030C (-P)	30,000	10.4 (11.6)	0.60	72.0
4030CS (-P)	30,000	10.6 (11.8)	0.65	78.0

4000C SERIES

Model	Description	Dimensions	Additional Amps	Additional Watts
4000CI(TR)	Touch Controller	6w x 6h x 4d	0.02	2.4
4000S	Sensor	6w x 6h x 4d	0.03	3.6



PROUDLY MADE IN THE USA



1865 Herndon Ave. Ste. K126 | Clovis, CA 93611
T 855.201.SAGE | www.SAGEINDUSTRIAL.com